

C1 PRACTIC & C11 PRACTIC PLUS

C1 PRACTIC: positioning belt

C11 PRACTIC PLUS: C1 PRACTIC + positioning lanyard (non-removable)



C1 PRACTIC



C11 PRACTIC PLUS

Certification	EN 358:2018 (belts and lanyards for work positioning or restraint) CE 2756
Webbing	Compact 30;
Buckles	CLASSIC (steel); 
Rings	WELDED 25 (Steel , BL > 25 kN);
Positioning lanyard (C11)	Standard length: 1,5 m (Max.) ; <i>*lengths up to 2 m on request</i> ; Rope: Ø12 mm, Kernmantle type; Length adjuster: aluminium; Connector: EN 362/T certified;
	Connector specifications: 022 KANGRI
	 Steel
	 25 kN
	 Auto Lock
	 238 g
	 18 mm
Sizes	<ul style="list-style-type: none"> • S-M (74 – 95 cm) • L-XL (90 – 120 cm) • XXL-XXXL (115 – 130 cm)
Max. 150 kg	C1 and C11 are tested and approved for users up to 150kg! (Max. 150 kg : user + equipment). Please follow using instruction manual!
Up to 10 years	Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in contact with oils, greases or aggressive chemicals, were not used extensively, can be hold in service for up to 10 years. Please follow using instruction manual!