

C3 RAPID & C3 RAPID SCAFF



C3 RAPID



C3 RAPID SCAFF

(C3 RAPID + dorsal extension strap 0,5 m)



Certification	EN 361 (full body harness) CE 2756	
Webbing	Compact 30;	
Buckles	Classic (Steel) 	Automatic: click type (Steel) 
Rings	WELDED 25 (Steel, BL > 25 kN)	
Available sizes	S-M , L-XL , XXL-XXXL	
„SCAFF” Version 	Extension strap “SCAFF”: -Materials: 45 mm webbing + metallic ring; -Total added length: 0,5 m; When using the SCAFF extension to compose a fall arrest system ALWAYS take into account its length (0,5 m), which is added to the final system ! BEFORE USE, READ THE INSTRUCTIONS CAREFULLY!	
Max. 150 kg	In this case, a suitable energy absorbing lanyard has to be used, so that the maximum force of the shock after an eventual fall, is reduced to less than 6 kN. (Max. 150 kg : user + equipment). Please follow using instruction manual!	
Up to 10 years	Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in contact with oils, greases or aggressive chemicals, were not used extensively, can be hold in service for up to 10 years. Please follow using instruction manual!	