

C4 DINAMIC & C41 DINAMIC PLUS

C4 DINAMIC: combined full body harness

C41 DINAMIC PLUS: C4 DINAMIC + adjustable positioning lanyard (non-removable)



C4 DINAMIC



C41 DINAMIC PLUS

Certification	EN 361 (full body harness) EN 358 (positioning belt) CE 2756
Webbing	Compact 30 (width 45mm);
Buckles	CLASSIC (Steel); 
Rings	WELDED D-Rings (Steel);
Positioning lanyard (C41)	Standard length: 1,5 m (Max.) ; *lengths up to 2 m on request; Rope: Ø12 mm, Kernmantle type; Length adjuster: aluminium; Connector: EN 362/T certified;
	Connector specifications: 022 KANGRI
	 Steel
	 25 kN
	 Auto Lock
	 238 g
	 18 mm
Available sizes	<ul style="list-style-type: none"> • S-M • L-XL • XXL-XXXL
Max. 150 kg	In this case, a suitable energy absorbing lanyard has to be used, so that the maximum force of the shock after an eventual fall, is reduced to less than 6 KN. (Max. 150 kg: user + equipment) Please follow using instruction manual!
Up to 10 years	Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in contact with oils, greases or aggressive chemicals, were not used extensively, can be hold in service for up to 10 years. Please follow using instruction manual!