

### V1 Neon / V11 Argon

V1 NEON – positioning belt;

V11 ARGON – positioning belt + positioning lanyard (non-removable);



V1 NEON Classic



V11 ARGON Classic

<b>Certification</b>	EN 358:2018 (belts and lanyards for work positioning or restraint) <b>CE 2756</b>	
<b>Webbing</b>	<b>CLASSIC:</b> Vertiqua standard 33 (BL > 3300 daN); <b>AUTOMATIC:</b> Vertiqua standard 33 Hi-Viz (BL > 3300 daN);	
<b>Buckles</b>	<b>CLASSIC</b> (Steel); 	<b>AUTOMATIC:</b> Smart-Lock "click" buckle (Alu); 
<b>Rings</b>	<b>CLASSIC:</b> Forged 40 (Steel); <b>AUTOMATIC:</b> Forged 40 (Steel); Standard length: <b>1,5 m (Max.)</b> ; <i>*lengths up to 2 m on request</i> ; Rope: Ø14 mm, Kernmantle type; Length adjuster: aluminium; Connector: EN 362/T certified	
<b>Positioning lanyard (V11)</b>		Steel
		25 kN
		Auto Lock
		238 g
		18 mm
		130/68 mm
	<b>Sizes</b>	<ul style="list-style-type: none"> <li>• S-M (74 – 95 cm)</li> <li>• L-XL (90 – 120 cm)</li> <li>• XXL-XXXL (115 – 130 cm)</li> </ul>
<b>Max. 150 kg</b>	V1 and V11 are tested and approved for users up to 150kg! (Max. 150 kg : user + equipment). <b>Please follow using instruction manual!</b>	
<b>Up to 10 years</b>	Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in contact with oils, greases or aggressive chemicals, were not used extensively, can be hold in service for up to 10 years. <b>Please follow using instruction manual!</b>	