

V4 XENON & V41 RADON

V4 XENON: combined full body harness

V41 RADON: V4 XENON + adjustable positioning lanyard (non-removable)



V4 XENON Classic



V41 RADON Classic

Certification	EN 361 (full body harness) EN 358 (positioning belt) CE 2756	
Webbing	Classic: Vertiqua Standard 33; Classic-Automatic: Vertiqua Standard 33;	
Buckles	 Classic (Steel);	 Classic-Automatic:click type(Steel);
Rings	Classic: Forged 40 (Steel); Classic-Automatic: Forged 40 (Steel);	
Positioning lanyard (V41)	Standard length: 1,5 m (Max.) ; <i>*lengths up to 2 m on request;</i> Rope: Ø14 mm, Kernmantle type; Length adjuster: aluminium; Connector: certified acc. to EN 362/T;	
	Connector specifications: 022 KANGRI	
		Steel
		25 kN
		Auto Lock
		238 g
		18 mm
	130/68 mm	
Available sizes	S-M , M-L , L-XL , XXL-XXXL	
Max. 150 kg	In this case, a suitable energy absorbing lanyard has to be used, so that the maximum force of the shock after an eventual fall, is reduced to less than 6 KN. (Max. 150 kg : user + equipment). Please follow using instruction manual!	
Up to 10 years	Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in contact with oils, greases or aggressive chemicals, were not used extensively, can be hold in service for up to 10 years. Please follow using instruction manual!	