

V53 ORBITER



Evo



Power & Comfort



Automatic



Classic / Classic-Automatic

<p>Certification</p>	<p>EN 361:2002 (full body harness) EN 358:2018 (positioning belt)</p> <p>CE 2756</p>
<p>Webbing</p>	<p>Evo: S-Guard TEFLON® (oil / dirt repellent); Allround: Vertiqua Standard 33 Hi-Viz; Power & Comfort: Platinum Safety Reflex Automatic: Vertiqua Standard 33 Hi-Viz; Classic: Vertiqua Standard 33; Classic-Automatic: Vertiqua Standard 33;</p>
<p>Buckles</p>	<p>Evo: COBRA® PRO-STYLE : click lock (Alu); Allround: COBRA® PRO-STYLE : click lock (Alu); Power & Comfort: AUTOMATIC-PREMIUM: click lock (Alu+Steel); Automatic: SMART-LOCK: click lock (Alu); Classic: CLASSIC: simple, with coupling plates (Steel); Classic-Automatic: CLASSIC-AUTOMATIC: click lock (Steel);</p>
<p>Rings</p>	<p>Evo: SPACE AERO 7 : B.L. > 30 kN (Alu); Allround: SPACE AERO 7 : B.L. > 30 kN (Alu); Power & Comfort: ANSI STEEL (Steel); Automatic: Forged 40 (Steel); Classic: Forged 40 (Steel); Classic-Automatic: Forged 40 (Steel);</p>
<p>Sizes available</p>	<p>S-M , M-L , L-XL , XXL-XXXL</p>
<p>Max. 150 kg</p>	<p>In this case, a suitable energy absorbing lanyard has to be used, so that the maximum force of the shock after an eventual fall, is reduced to less than 6 KN. (Max. 150 kg : user + equipment)</p> <p>Please follow using instruction manual!</p>
<p>Up to 10 years</p>	<p>Safety harnesses belonging to a single user, which were subject to periodical inspections by experts and recorded in the Inspection Log, carefully treated and maintained, were stored in accordance with regulations, were not in contact with oils, greases or aggressive chemicals, were not used extensively, can be hold in service for up to 10 years.</p> <p>Please follow using instruction manual!</p>